



**MATERIAL SAFETY DATA SHEET**  
**SUPERIOR SUPERSAFE<sup>®</sup> No. 30 Paste**

DATE REVISED: January 1, 2009



**Product Name:** Superior No. 30 Paste

**Manufacturer:** Superior Flux & Mfg. Co. 6615 Parkland Blvd. Cleveland, OH 44139

**Emergency Phone Number:** 1-800-424-9300 (CHEMTREC)

**Other Information Calls:** (440) 349-3000

**To the Purchaser:** This MSDS contains important environmental, health, and toxicology information for your employees who have ordered this product. Please be sure this information is given to them. If you resell this product, a copy of the MSDS should be given to the buyer.

**H.M.I.S. INFORMATION: HEALTH = 1      FLAMMABILITY = 0      REACTIVITY = 0**

**SECTION I - IDENTIFICATION**

**Common Name:** Superior Supersafe<sup>®</sup> No. 30 Paste      **Chemical Family:** Organic Acid Soldering Flux

**CAS Number:** NA

**Chemical Name:** NA

**Formula:** See Below

**SECTION II - COMPOSITION INFORMATION**

<u>Components</u>	<u>CAS Number</u>	<u>%</u>	<u>OSHA PEL</u>
Glutamic Acid Hydrochloride	138-15-8	5-10	NA

Unlisted percentages are non-hazardous stabilizers, activators, and water. None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

**SECTION III - HEALTH HAZARDS**

**EMERGENCY AND FIRST AID PROCEDURES**

**Eyes:** Flush with Water for 10 Minutes. Call a Physician.

**Skin:** Wash Thoroughly with Water.

**Inhalation:** Remove to Fresh Air or Administer Oxygen. Call Physician.

**Ingestion:** Give Water or Milk. Get Medical Attention.

**Primary Routes of Entry:** Fume Inhalation, Ingestion, Skin, and Eyes.

**Symptoms of Overexposure:** No Specific Information Available.

**Medical Conditions Generally Aggravated by Overexposure:** None Presently Known.

**Chemical Listed as a Carcinogen or Potential Carcinogen:** None

**OSHA Permissible Exposure Limit (PEL):** 5 mg/m<sup>3</sup>

**ACGIH Threshold Limit Value (TLV):** 5 mg/m<sup>3</sup>

*Superior manufactures quality fluxes. Our business is solving problems.*



**Superior Flux  
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003  
[www.superiorflux.com](http://www.superiorflux.com) • e-mail: [info@superiorflux.com](mailto:info@superiorflux.com)

#### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** NA **Flammable Limits:** NA  
**Extinguishing Media:** Not Necessary **Auto Ignition Temperature:** None  
**Special Fire Fighting Procedures:** Normal Cautions when Dealing with Chemicals.  
**Unusual Fire and Explosion Hazards:** Will Release Small Amounts of HCl.

#### SECTION V - ACCIDENTAL RELEASE MEASURES

**Steps to be Taken in Case Material is Spilled:** First Neutralize with Soda Ash or Sodium Bicarbonate, Dilute with Water and Dispose of in Accordance with EPA Regulations and Wash with Plenty of Water.

#### SECTION VI - HANDLING AND STORAGE

**Storage Requirements:** Store in Plastic Containers in Cool Area, Away From Heat.  
**Handling Precautions:** Safe Precautionary Practices to Avoid Spills and Exposure to Skin and Fumes.

#### SECTION VII - CONTROL MEASURES

**Respiratory Protection (TYPE):** NIOSH Approved Respirator. **Ventilation:** Yes  
**Mechanical (General):** Yes **Local Exhaust:** Yes  
**Eye Protection:** Safety Glasses/Goggles  
**Protective Gloves:** Recommended, NIOSH Approved  
**Other Protective Clothing or Equipment:** Optional to User's Preference

#### SECTION VIII - PHYSICAL AND CHEMICAL CHARACTERISTICS

**Boiling Point:** NA **Specific Gravity (Water = 1):** NA  
**Vapor Pressure (mm Hg):** NA **Percent Volatile by Volume:** NA  
**Vapor Density (Air = 1):** NA **Evaporation Rate (Butyl Acetate = 1):** NA  
**Melting Point:** NA **Solubility in Water:** Unlimited  
**Reactivity in Water:** None **Appearance and Odor:** Blue Paste, Citrus Odor

#### SECTION IX - STABILITY AND REACTIVITY

**Stability:** Product is Stable **(Conditions to Avoid):** NA  
**Incompatibility:** Strong Oxidizers, Metals.  
**Hazardous Decomposition Products:** Small Amounts of HCl.  
**Hazardous Polymerization:** Will Not Occur **(Conditions to Avoid):** NA

#### SECTION X - TRANSPORTATION AND DISPOSAL CONSIDERATIONS

**D.O.T. Proper Shipping Name:** Non-Hazardous **Hazard Class:** NA  
**Identification Number:** NA **Packing Group:** NA  
**Type D.O.T Label Required Information:** NA  
**Waste Disposal Method:** Dispose of in Accordance with EPA Regulations  
**This Product is RoHS Compliant.**

**Disclaimer:** Judgments as to the suitability of information herein or the purchaser's purposes are necessarily the purchaser's responsibility. Reasonable care has been taken in the preparation of this material, but there are NO WARRANTIES, NO REPRESENTATIONS, AND NO RESPONSIBILITY AS TO THE ACCURACY OR THE SUITABILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCE TO USE.

MSDS: Superior No. 30 Paste p2/2

The information contained herein is based on data considered to be accurate and is intended for use by persons having technical skills at their own discretion and risk. Since conditions of use are outside of Superior Flux & Mfg. Co.'s control, we cannot assume liability for results obtained or damage incurred due to misuse, nor can we assume customer liability.

*Superior manufactures quality fluxes. Our business is solving problems.*



**Superior Flux  
& Mfg. Co.**

6615 Parkland Blvd. • Cleveland, OH 44139 • Phone: 440-349-3000 • Fax: 440-349-3003  
[www.superiorflux.com](http://www.superiorflux.com) • e-mail: [info@superiorflux.com](mailto:info@superiorflux.com)